



Regular Diesel

TATSUNO			
\$	30.00	THIS SALE	20.00 \$
\$	20.27	LITERS	14.82 \$
\$	1.48	PRICE / LITER	1.35 \$

Press instructions	EMERGENCY STOP	Press instructions
1 Press to start		1 Press to start
2 Press to stop		2 Press to stop
3 Press to cancel		3 Press to cancel
4 Press to help		4 Press to help

Sunny-GII
Dispensing Pump 222
TATSUNO

Regular

TATSUNO	
THIS SALE	20.00 \$
LITERS	13.51 \$
PRICE / LITER	1.48 \$

Sunny-GII
Dispensing Pump III
TATSUNO

Sunny-GII

GENERATION
Dispensing Pump & Dispenser PAT.PEND.

TATSUNO
In Innovation, In Reliable Services

Highly reliable popular dispenser
equipped with global-standard components

Sunny-GII

GENERATION
Dispensing Pump & Dispenser PAT.PEND.



- Meets OIML standards and achieving optimum balance of excellent performance economically
- Compact body fits into narrow spaces

Equipped with reliable,
high-precision
Tatsuno pump/meter



Long-lasting, A fine display uses high-visibility bright red LED backlight



- Large, easy-to-read characters and compact layout
- Supports up to 5-digit unit price and 7-digit money amount & volume

Standard-equipped with user-friendly preset keypad



Secure, password-protected registration

Standard-equipped with over-voltage protector (OVP) to protect electrical device from high voltage

Supported by full range of options

- Non-resettable electromagnetic totalizer
- Emergency stop switch ● POS interface (RS-485)
- Sight glass ● Double swivel ● Safety coupling
- Emergency shut-off valve ● Full range of nozzle options ● Reusable filter
- High-speed: 70 L/min Maximum speed: 80 L/min ● Top gallery panel



Types

2222




1222



1111



Dimensions



Specifications

Delivery Speed	Standard speed (Gasoline/Diesel) : 40 L/min High speed (Diesel) : 60~70 L/min ※Manual drive is not provided ※Delivery speed is fluctuate by installed components (Suction Type) ※Delivery speed is fluctuate by STP and installed components (Remote Type)
Suction Head (Suction Type)	4 m (Gasoline Column)
Measuring Accuracy	+/- 2.5/1000
Display Type	Micro-computer type electronic counter at non-hazardous area
Price and Volume Indication	Price : 7 digits 0.01~ 99,999.99 Volume : 7 digits 0.01~ 99,999.99 Unit Price : 5 digits 0.01~ 999.99 ※Decimal places is possible to change according to each local specification.
Size of Display Character	Price Readout : 30H x 120W mm Volume Readout : 30H x 120W mm Unit Price Readout : 24H x 98W mm
Color of Display Character	Black characters with LED backlight. (LCD)
Reset	Automatic Reset
Totalizer	Electronic : 10 digits 99 999 999.99 Liters (Displayed on counter)
Daily Totalizer	Electronic : 10 digits 99 999 999.99 Liters (Displayed on counter)
Keypad	Volume and amount preset can be set up from dispenser. Numeric key only
Over Voltage Protector	Standard support
Self-Diagnosis	Standard support
Initial-setting Method	By using keypad
Pulser	0.01 L/pulse
Pump (Suction Type)	Internal Silent Gear Pump with air separator, by-pass valves, suction strainer and check valves
Meter	4-Piston Type Positive Displacement Meter with micro-minute adjuster for manual calibration
Flow Control Valve	Solenoid Valve
Motor (Suction Type)	Explosionproof, Continuous duty motor with over load Protection 3-Phase 1 HP (380 V) 1-Phase 1 HP (220 to 240 V)
Filter (Submersible Type)	Paper filter
Hose	3/4" x 15 ft
Nozzle	3/4" Automatic stop nozzle
Swivel	Single Swivel

Note : The delivery speed of the pump may change due to the following conditions if it is used beyond Tatsuno' s installation and operational instructions :

- 1) Size and length of hose
- 2) Size and type of nozzle/swivel
- 3) Oil products, suction condition, and local piping conditions

Specifications are subject to change with or without prior notice.



International Marketing Dept.

1-1, Kasama 4-Chome, Sakae-ku, Yokohama, 247-8570, Japan
Telephone:+81-(0)50-9000-0555 Fax:+81-(0)45-893-4680

<http://www.tatsuno.co.jp/>