

World-class Industrial Oil Dispensing Pumps with guaranteed performance & hassle free operation

Pumps are designed to work in tough conditions & are ideal for use in Industry, workshop, farm, construction or as part of the Mobile Oil system

All metal construction, fully CNC machined with hardened wear resistant moving parts

Reciprocating piston operated 2-1/2" (63 mm) dia. Air Motor

Stub Pumps are supplied with Non Return Valve threaded 1" (F) for use on the bottom of the Suction Tube.

Other pump lengths have a built in strainer at pump inlet to keep contaminants away

WETTED COMPONENTS

Steel, Brass, Aluminum, Zinc, Hi Nitrile Rubber, Polyurethane, Turcite* & Nylon**

(*Only on 3:1 & 5:1 pumps,

** Only on 1:1 pumps)

SPECIFICATIONS

WORKING PRESSURE	30 - 150 PSI (2 - 10 BAR)
MAX. AIR PRESSURE	150 PSI (10 BAR)
AIR INLET CONNECTION	1/4" BSP (F) / 1/4" NPT (F)
PUMP OUTLET CONNECTION	1/2" BSP (F) / 1/2" NPT (F)
PUMP INLET ON STUB PUMPS ONLY	1" BSP (F) / 1" NPT (F)
NOISE LEVEL	81 db

WARNING

Pump must be supplied with clean & dry compressed air via an FRL unit

GROZ also manufactures Wall Mounting Bracket for Stub Pumps, refer to page 144 for details



<< Pump Internals



VARIANTS - 1:1 PUMPS

Transfer pump, used for quick transfer of oils from large drums to smaller containers. These have a **Double Acting Operation** with discharge upto 40 LPM (10.58 GPM).

Ideal for use with low to medium viscosity oils (upto SAE 80) for transfer over short distances (5 metres)

Air Consumption: 270 LPM (71.5 GPM)

Also available complete with Oil Bar Tap & connecting links (ODS series), used as an Air Operated Oil Dispenser to quickly & conveniently dispense Oils from Drums.

FEATURES

DELIVERS

UPTO
40 LPM
(10.5 GPM)



OP/S/11B/BSP



Double Acting



ODS/T3/11B/BSP

ORDERING INFORMATION

CAT NR.	ORD NR.	CAT NR.	ORD NR.	DESCRIPTION	BOX QTY.
BSP THREADS		NPT THREADS			
OP/S/11B/BSP	45322	OP/S/11B/N	45323	Stub Pump with Bung Adaptor and Foot Valve	4
OP/T2/11B/BSP	45332	OP/T2/11B/N	45333	Pump complete with Suction Tube for 16 gal (50-60 litre) drums & bung adaptor	4
★ OP/T3/11B/BSP	45342	★ OP/T3/11B/N	45343	Pump complete with Suction Tube for 55 gal (205 litre) drums & bung adaptor	4
ODS/T3/11B/BSP	45355	ODS/T3/11B/N	45356	Pump complete with Suction Tube for 55 gal (205 litre) drums, bung adaptor, Oil Bar Tap & fittings	4

★ Best Seller

OP-11

OP-31

ODS-11

OP-51

VARIANTS - 3:1 PUMPS

Amongst the most popular general purpose air operated pumps worldwide

Pumps are single acting with discharge upto 14 LPM (3.70 GPM)

Ideal for use with medium to high viscosity oils (upto SAE 130) for transferring over short distances (upto 30 metres), mostly used with Trolley mounted kits

Air Consumption
230 LPM (61 GPM)

FEATURES

DELIVERS

UPTO
14 LPM
(3.70 GPM)

**OP/T3/31B/N****ORDERING INFORMATION**

CAT NR.	ORD NR.	CAT NR.	ORD NR.	DESCRIPTION	BOX QTY.
BSP THREADS		NPT THREADS			
OP/S/31B/BSP	45320	★ OP/S/31B/N	45321	Stub Pump with Bung Adaptor and Foot Valve	4
OP/T2/31B/BSP	45330	OP/T2/31B/N	45331	Pump complete with Suction Tube for 50-60 litre (16 gal.) drums & bung adaptor	4
★ OP/T3/31B/BSP	45340	★ OP/T3/31B/N	45341	Pump complete with Suction Tube for 205 litre (55 gal.) drums & bung adaptor	4

★ Best Seller

VARIANTS - 5:1 PUMPS

High Pressure pumps for dispensing oil at 5 times the pressure as the air inlet

Double Acting

With discharge upto 18 LPM (4.76 GPM)

Ideal for use with high viscosity oils (upto SAE 240) for transferring over short & long distances (upto 50m)

Mostly used with Trolley mounted kits both with & without Hose Reels, as well as with fixed systems for centralized distribution

Air Consumption
250 LPM (66 GPM)

FEATURES

DELIVERS

UPTO
18 LPM
(4.76 GPM)

Double Acting

**OP/S/51B/N****ORDERING INFORMATION**

CAT NR.	ORD NR.	CAT NR.	ORD NR.	DESCRIPTION	BOX QTY.
BSP THREADS		NPT THREADS			
OP/S/51B/BSP	45324	★ OP/S/51B/N	45325	Stub Pump with Bung Adaptor and Foot Valve	4
OP/T2/51B/BSP	45334	OP/T2/51B/N	45335	Pump complete with Suction Tube for 16 gal (50-60 litre) drums & bung adaptor	4
★ OP/T3/51B/BSP	45344	★ OP/T3/51B/N	45345	Pump complete with Suction Tube for 55 gal (205 litre) drums & bung adaptor	4

★ Best Seller