

3:1 Air Operated Stainless Steel Pump

Suitable for use with water based fluids, detergents, water etc. in garages workshops, car washers, lube trucks, industrial applications etc.

Wetted components are made out of Stainless Steel for protection against corrosion

Reciprocating piston operated 2-1/2" (63 mm) dia. Air Motor

Built in Stainless Steel Strainer at inlet keeps contaminants away

Includes 2" Die Cast Aluminium bung for use with 205 Litre (55 gallons) drums

WETTED COMPONENTS

Stainless Steel, Brass, Aluminium, Hi-Nitrile Rubber, Polyurethane, Turcite

RECOMMENDED USE

Water, water soluble lubricants, coolants, soap solutions, detergents, windshield fluids etc.

DO NOT USE

Food Grade media, waste oil or any media not compatible with the pump components

SPECIFICATIONS

WORKING PRESSURE	2 - 10 BAR (30 to 150 PSI)
MAX. AIR INLET PRESSURE	10 BAR (150 PSI)
MAX. MEDIA OUTLET PRESSURE	450 PSI (30 BAR)
AIR CONSUMPTION	230 LPM (61 GPM)
AIR INLET CONNECTION	1/4" BSP (F) / 1/4" NPT (F)
PUMP OUTLET CONNECTION	1/2" BSP (F) / 1/2" NPT (F)
NOISE LEVEL	81 db

FEATURES
DELIVERS

**UPTO
14 LPM
(3.70 GPM)**

ORDERING INFORMATION

CAT NR.	ORD NR.	DESCRIPTION	BOX QTY.
OP/T3/SS/BSP	45360	Pump complete with suction tube for 205 litre (55 gallon) drums	4
◆ OP/T3/SS/N	45365	Pump complete with suction tube for 205 litre (55 gallon) drums	4

◆ New



Stainless steel
suction tube

Stainless
steel strainer

WARNING

Pump must be supplied with clean & dry compressed air via an FRL unit